


Spiral Strand Specification Chart (Imperial)



Part #	Nominal Diameter (in)	Approx Weight (lb/ft)	Approx Metallic Area (in ²)	Grade 1 Class A Throughout	Grade 1 Class C Outer Wires	Grade 2 Class A Throughout
				Minimum Breaking Strength (tons of 2,000 lbs)		
WSS - 200	1/2	0.52	0.15	15.0	14.2	17.3
WSS - 203	5/8	0.82	0.23	24.0	22.8	27.6
WSS - 206	3/4	1.18	0.34	34.0	32.3	39.1
WSS - 209	7/8	1.61	0.46	46.0	43.7	52.9
WSS - 212	1	2.10	0.60	61.0	57.9	70.2
WSS - 215	1 1/8	2.66	0.76	78.0	74.1	89.7
WSS - 218	1 1/4	3.28	0.94	96.0	92.2	110
WSS - 221	1 3/8	3.97	1.13	116	111	133
WSS - 224	1 1/2	4.73	1.35	138	132	159
WSS - 227	1 5/8	5.55	1.59	162	155	186
WSS - 230	1 3/4	6.43	1.84	188	180	216
WSS - 233	1 7/8	7.39	2.11	216	207	248
WSS - 236	2	8.40	2.40	245	238	282
WSS - 239	2 1/8	9.49	2.71	277	269	319
WSS - 242	2 1/4	10.64	3.04	310	301	357
WSS - 245	2 3/8	11.85	3.38	344	334	396
WSS - 248	2 1/2	13.13	3.75	376	365	432
WSS - 251	2 5/8	14.47	4.13	417	404	480
WSS - 254	2 3/4	15.88	4.54	452	438	520
WSS - 257	2 7/8	17.36	4.96	494	479	568
WSS - 260	3	18.90	5.40	538	522	619
WSS - 263	3 1/8	20.51	5.86	584	566	672
WSS - 266	3 1/4	22.18	6.34	625	606	719
WSS - 269	3 3/8	23.92	6.83	673	653	774
WSS - 272	3 1/2	25.73	7.35	724	702	833
WSS - 275	3 5/8	27.60	7.88	768	745	883
WSS - 278	3 3/4	29.50	8.43	822	797	945
WSS - 281	3 7/8	31.50	9.00	878	852	1010
WSS - 284	4	33.60	9.60	925	897	1064

Other diameters available upon request



2400 W. 75th Street
Prairie Village, KS 66208
T (816) 270-4700
info@wireco.com
www.wireco.com